



Mobile 750 kVA dynamic UPS system, with 2 coupled units of 500 kVA of which the output power is adjusted to 750 kVA. The system is built in a standard sound isolated ISO container and mounted on a trailer for easy transportation, including all necessary auxiliaries.

<b>Power</b>	750 kVA – 600 kW (cos phi 0,8) – 400V
<b>Frequency</b>	50 Hz
<b>Dimensions</b>	2 units of 13,3 x 2,4 x 4m (LxBxH) placed side by side in length or width
<b>Weight</b>	2 x 28 000 kg
<b>Fuel tank</b>	2 x 1000 liters
<b>Autonomy</b>	13u at full load
<b>Max. ambient temperature</b>	40°C
<b>Max. relative humidity</b>	90%
<b>Sound level at 10m</b>	60 dB(A) in normal operation 75 dB(A) at half load emergency operation 80 dB(A) at full load emergency operation
<b>Positioning</b>	Hard standing surface 2 x 1 x 0,4 m clearance on all sides (LxWXH)

### Including

- Diesel engine
- Noise reduction in compliance with European standards
- Built-in fuel tank for long autonomy
- Easy cabling
- Integrated exhaust, cooling and fuel systems
- Transport, cabling, installation, commissioning and engineering support
- Different rental formulas
- 24h service
- No exceptional transport

### Benefits for you

- Environment friendly: no batteries, low consumption and low emissions
- Active filter against mains pollution
- Easy transport
- Robust and compact